

FEATURES



High-precision GPS/GLONASS tracking device



Weatherproof and ultra-rugged IP67 Nylon Glass Housing with compact and ergonomic design



Powered by 3 x AA Batteries with up to 5 years battery life



Accelerometer for Smart Movement Based Tracking



Oyster LoRaWAN®

ALL 868MHZ & 915MHZ LORAWAN® REGIONS SUPPORTED

OVERVIEW

Ultra-rugged and long-life battery-powered LoRaWAN® GPS tracking device for long-term asset tracking.

APPLICATIONS



Asset Tracking



Theft Recovery



Run Hours Monitoring



Preventative Maintenance

CONNECTIVITY

LoRaWAN®	Highly sensitive radio receiver available in 868MHz and 915MHz versions for global LoRaWAN® connectivity.
LoRaWAN® REGIONS	AU915 AS923 EU868 IN865 KR920 RU864 US915

BATTERIES

USER-REPLACEABLE BATTERIES	3 x AA
BATTERY LIFE	Up to 5 years of battery life at once-daily heartbeats.
SUPPORTED BATTERY TYPES	Alkaline Lithium (LiFeS2) - recommended

LOCATION

MODULE	uBlox MAX8
CONSTELLATION	Concurrent GPS / GLONASS
CHANNELS	72 Channel High Sensitivity Receiver
TRACKING SENSITIVITY	-167dBm industry-leading tracking performance
LOW NOISE AMPLIFIER	GPS signals are boosted by a unique low-noise amplifier (LNA) allowing operation where other units fail.

POWER

INPUT VOLTAGE	4-6V DC
SLEEP CURRENT	<10uA* *Average current in lowest power configuration

MECHANICS/DESIGN

DIMENSIONS	L 108 x W 86 x H 31mm
WEIGHT	188g
HOUSING	Ultra-Rugged Nylon Glass
IP RATING	IP67 rated housing ensures device can withstand fine dust, high-pressure spray, submersion for 30 mins in 1m of water, and extreme temperatures.
INSTALLATION	Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more.
OPERATING TEMPERATURE	-20°C to +60°C
GPS ANTENNA	Internal
3-AXIS ACCELEROMETER	3-Axis Accelerometer to detect movement.
DIAGNOSTIC LED	Diagnostic LED signifies operation status.

SMARTS

GEOFENCING	Create custom geofences and alerts if an asset enters or leaves specific locations.
PERIODIC OR MOVEMENT-BASED	Configure parameters to send updates based on set time intervals (1x, 3x, 5x a day, etc) or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary.
SLEEP MODE	Stationary devices enter sleep mode, switching the update rate to only once per day until movement occurs to conserve battery life and optimize data usage.

DEVICE MANAGEMENT

FLEXIBLE CONFIGURATION	Configure device parameters such as heartbeat rate, movement and accelerometer settings, and more to fit any tracking application.
CONFIGURATION APP	Manage device firmware updates and parameters via a USB configuration cable and app. Some parameters can be changed via downlink.

INTEGRATION

THIRD-PARTY INTEGRATION	Easy integration with comprehensive documentation and a flexible and open payload format.
-------------------------	---

SECURITY

DATA SECURITY	LoRaWAN® networks use AES-128 Encryption so your data is protected.
---------------	---

WARRANTY

MANUFACTURER'S WARRANTY	One year manufacturer's warranty.
-------------------------	-----------------------------------

CERTIFICATIONS

Please contact us for a full list of compliance specifications and documentation for your region.	915MHz - FCC, ISED, ACMA (DoC), CE (DoC), LoRaWAN Certified(CM) 868MHz - ACMA (DoC)
---	--

Oyster LoRaWAN®

View more devices at www.digitalmatter.com

TECH SPECS